

**Kun typetegning.
Ikke mål på tegningen.**

Dimensjoner / Type / Kapasiteter

Størrelse/ Type (Ø mm)	Stål- kvalitet. (N/mm ²)	Stål- areal. (mm ²)	Flyte- kapasitet. (kN)	Brudd- kapasitet. (kN)	Dim.kap. 0,60 x F _u (kN)
R51-950**	-	1225	775	950	570
R51-800	570/720	1150	640	800	480
R51-660	540/670	970	540	660	396
R51-550	510/630	878	450	550	330
R38-550	550/710	890	450	550	330
R38-500	530/660	750	400	500	300
R38-420	510/610	660	350	420	252
R32-400	-	560	330	400	240
R32-360	590/710	510	280	360	216
R32-320	590/680	470	250	320	192
R32-280	520/670	410	220	280	168
R32-250	510/670	370	190	250	150
R32-210	530/660	340	160	210	126

Størrelse/ Type (Ø mm)	Kuppelplate		Flat plate	
	Dim (mm)	Tykkelse (mm)	Dim (mm)	Tykkelse (mm)
R51-950**	-	-	200x200	35
R51-800	200x200	20	200x200	35
R51-660	200x200	15	200x200	35
R51-550	200x200	15	200x200	35
R38-550	200x200	15	200x200	30
R38-500	200x200	15	200x200	30
R38-420	200x200	12	200x200	30
R32-400	200x200	12	200x200	20
R32-360	200x200	12	200x200	20
R32-320	200x200	12	200x200	20
R32-280	200x200	10	200x200	20
R32-250	150x150	8	200x200	20
R32-210	150x150	8	200x200	20

** ETA gjelder ikke R51-950



Rotasjons adapter
(Rigg installasjon)



Rotasjons adapter
(Rigg installasjon)



Injeksjons adapter



Air flush shaft
(håndholdt installasjon)



Ekspansjonsbolt for R32 og R38

DYWI® Drill er ETA godkjent.